



CB-2 (CBO-2000 120 Volt or CBO-2002 240 Volt) Circle Burner

For straight or beveled flame cut holes on large diameter pipe and vessels, without wrap-up of power cable or gashoses (120/50-60/1 240/50-60/1).

Mounts on workpiece using powerful, permanent ON/OFF magnet.

Features:

- Permanent magnet motor.
- Brushes and collector rings for power supply.
- Manual ON/OFF hold down magnet.
- Rack and pinion adjustment of torch, vertical and horizontal.
- 2-hose machine torch with one tip [specify fuel gas].

Capacities:

- For square cut holes: 4"-48" (100-1220 mm).
- For bevel cut holes: 1.5"-42" (40-1067 mm).
- 100% duty cycle.
- 0-7" (0-175 mm) rise and fall cam.
- Rotation speed 3-160 ipm (76-4064 mm/min).

Controls:

- Rotation, FWD-OFF-REV switch.
- Rotation speed control.
- Pre-heat gases.
- Cutting oxygen.
- Pilot light.
- Fuse.

Technical Data:

CB-2 (CBO-2000 CBO-2002)

Height: 37" (940 mm).
Net Weight: 210 lbs. (95 kg.)
Shipping Weight: 290 lbs. (132 kg.)

