

For straight or beveled flame cut holes on domed heads, vessels and large diameter pipe, without wrap-up of power cable or gas hoses (120/50-60/1).

Mounts on carriage or manipulator.

#### Features:

Permanent magnet motor

2-hose machine torch with one tip [specify fuel gas]

Brushes and collector rings for power supply

Rack and pinion adjustment of torch, vertical

and horizontal

50 ft. (15.24 m) control cable

Adjustable, mechanical rise and fall

# **Capacities:**

For square cut holes: 4"-48" (100-1220 mm)

For bevel cut holes: 1.5"-42" (40-1060 mm)

100% duty cycle

0-7" (0-175 mm) rise and fall cam

Rotation speed 0.1-2 rpm

## **Controls:**

Rotation, FWD-OFF-REV switch

Rotation speed control

Pre-heat gases (on torch)

Cutting oxygen (on torch)

Pilot light

Fuse

### **Available Options:**

Harris Torch

Center Shaft for 3-Hose Torch


Motorized Racking


Increased Rise & Fall Cam


### **Technical Data:**

CB-3 (CBO-3000) 120 VAC CB-3 (CBO-3002) 240 VAC

**Height:** 37" (940 mm). **Net Weight:** 170 lbs. (77 kg.)







Includes hillside attachment for burning on and off centerline holes.

Mounts on column and boom or manipulator.

## Features:

Permanent magnet motor

2-hose machine torch with one tip [specify fuel gas]

Brushes and collector rings for power supply

Rack and pinion adjustment of torch, vertical and horizontal

Hillside attachment for burning on and off centerline holes

# Capacities:

For square cut holes: 4"-48" (100-1220 mm) For bevel cut holes: 1.5"-42" (40-1060 mm)

100% duty cycle

0-7" (0-175 mm) rise and fall cam

Rotation speed 0.1-2 rpm

#### **Controls:**

Rotation, FWD-OFF-REV switch

Rotation speed control

Pre-heat gases (on torch)

Cutting oxygen (on torch)

Pilot light

Fuse

# **Available Options:**

Harris Torch

Center Shaft for 3-Hose Torch

Motorized Racking

Increased Rise & Fall Cam

### **Technical Data:**

# CB-3H (CBO-3010) 110 VAC\*

**Height:** 37" (940 mm). **Net Weight:** 180 lbs. (82 kg.)

\*240 VAC available upon request

